PUROZONE

SANIFICATOR

FARO

EXPERIENCE AND INNOVATION
SINCE 1948

PUROZONE
SANIFICATOR

The **Made in Italy** solution, powerful, reliable and eco friendly, to sanitize air and surfaces.
Robust, **effective** and **efficient**, it's the perfect technology for complete hygiene and preventionin the dental clinic.

PROTECT YOUR PEOPLE, PROTECT YOURSELF.

SANITIZE	air and surfaces from pathogens, virus, bacteria, parasites, allergens, yeast and mold spores.
REPEL	insects, mites, fleas, ticks, lice, moths, cockroaches and mosquitoes.
PURIFY	every material, neutralizes odors and regenerates the air.

THE REASONS WHY

1. ECO-FRIENDLY no chemical detergents required.
2. EFFECTIVE on air and hidden surfaces.
3. SAFE for materials and planet.
4. APPROVED by Food and Drug Administration and Minister of Health of Italy.
Ozone is recognised as the natural solution against bacteria, virus and spores.

FULL TRACEABILITY

Integrated printer to reproduce on thermal paper all the details: model of machine, date, start and end time for cycle and result.
The total amount of hours and cycles performed are also available for printing.

USER-FRIENDLY

PurOZONE manages the optimal amount of Ozone and duration for each sanitizing cycle by itself, without the user intervention. It keeps cheking the Ozone concentration in the room, **converting any excess into Oxygen without risk**, leaving no trace.

3 PROGRAMS: PICK THE BEST FOR YOU

STANDARD	The optimum level of Ozone is reached (**saturation**) and kept for 20 minutes (**stabilization time**) before the reduction of excess Ozone starts.
SHORT	The optimum concentration of Ozone is set by the user and stable in the room up to 20 minutes. Then the reduction process of excess Ozone starts. Recommended in any treatement break OR between every patient.
MANUAL	The device keeps supplying Ozone until the user stops it.

1.	**PRESS THE GREEN BUTTON**	**WAIT FOR THE ACOUSTIC SIGNAL**	**LEAVE THE ROOM**
2.	**WAIT FOR THE OZONE PRODUCTION*** 20 MINUTI 20 minutes - recommended time for stabilisation and sanification		
3.	**CONVERSION OF OZONE TO OXYGEN** wait for the beep and get back in the room		

*Time recommended by the Italian Ministry of Health for maintaining the optimal level of Ozone. It does not refer to the total duration of the cycle which depends on the environment in which it is used the machine.

TECHNICAL FEATURES**

TECHNOLOGY	Generator with corona effect with ceramic plates
DIMENSIONS (LxWxH)	380x175x120 mm
SCREEN SIZE	0,96 Inches
POWER CONSUMPTION	max 120 W
POWER SUPPLY	220V 50/60Hz
OZONE SUPPLY	3,5 gr/h
STANDARD CYCLE TIME	45' for 20sq
WEIGHT	5,2 Kg

Typical data subject to tolerance. In Compliace with Directives 2014/35 UE - 2014/30 UE.
** The total duration of the cycle depends on the environment in which the machine is used.

CE
Medical Device compliant 0051 with Directive 93/42/CEE

M92001704_rev0_ENG

FARO
EXPERIENCE AND INNOVATION SINCE 1948

FARO S.p.A.
Via Faro, 15 - 20876 Ornago (MB) Italy
Tel. +39 039.68781
www.faro.it
export@faro.it

FARO FRANCE
Avenue de l'Europe - 71 210 ECUISSESS France
Tel. +33 385.779680
www.farofrance.com
farofrance@farofrance.com

FARO DEUTSCHLAND GMBH
Gewerbepark Heideckhof Heideckstr. 179
D-47805 Krefeld - Germany
Tel. +49 2151.936921
www.farodeutschland.de
info@farodeutschland.de

INFO LINE: